



STYLE
7400 / 7450

7400 - BLACKOUT FABRIC
7450 - LIGHT-FILTERING FABRIC

WEAVING
EXCELLENCE
WITH
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
STYLE 7400 - BLACKOUT							
U80	Cotton	0	64	36	0	0.27	0.21
U87	Flint	0	64	36	0	0.27	0.21



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



MIF Seal of Approval



STYLE 7400

TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorptance
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values, test
references and technical definitions visit
us at phifer.com.



STYLE
7400

U80
Cotton

U81
Parchment

U82
Sesame

U83
Pebble

U85
Shale

U84
Seagrass

U86
Spice

U87
Flint



STYLE
7450

U80
Cotton

U81
Parchment

U82
Sesame

U83
Pebble

U85
Shale

U84
Seagrass

U86
Spice

U87
Flint

STYLE 7400 / 7450 SPECIFICATIONS

A picture of refined elegance, Style 7400 layers a subtle textured pattern over a soft, luxurious backing for total light blockage. Offering the face fabric of Style 7400, Style 7450 filters natural light while illuminating interior spaces. These fabrics are suitable for roller shades, Roman shades and panel track systems.

STYLE 7400 FIRE CLASSIFICATION California U.S. Title 19 (small scale) NFPA 701 TM#1 (small scale)
CAN/ULC-S 109 (large and small scale) NFPA 701 TM#2 (large scale)
CAN/CGSB2-4.162-M80

STYLE 7450 FIRE CLASSIFICATION California Technical Bulletin 117 NFPA 101 (Class A Rating)
IBC Section 803.1.1 (Class A Rating)

Fire classifications are subject to change. Please go to phifer.com for the most current information.

BACTERIA AND FUNGAL RESISTANCE ASTM G21-96 AATCC 174-1998 Part II and III

ENVIRONMENTAL CERTIFICATION GREENGUARD GREENGUARD Gold
Certified to these standards for low chemical emissions into indoor air during product usage

SAFE USE RoHS/Directive 2002/95/EC
ANSI/WCMA A 100.1-2007 for lead content
US Consumer Product Safety Commission Section 101

WARRANTY 5-year interior

ACOUSTICAL PERFORMANCE NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a

UV PROTECTION Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes

CLEANING INSTRUCTIONS Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

Railroading this fabric is not recommended.

Colors may vary slightly from swatch samples. All variations are within industry standards.

STYLE	7400	7450
WIDTHS	118" 300 cm	118" 300 cm
ROLL LENGTH	30 Linear Yards 27.4 Linear Meters	30 Linear Yards 27.4 Linear Meters
COMPOSITION	100% Polyester with Acrylic Foamed Backing	100% Polyester with Acrylic Coating
MESH WEIGHT	12.53 oz/yd ² 425 g/m ²	6.54 oz/yd ² 221 g/m ²
FABRIC THICKNESS	0.029 in 0.74 mm	0.026 in 0.66 mm
OPENNESS FACTOR	Opaque	Light-filtering
ACOUSTICAL VALUE	NRC .05 / SAA .03	NRC .25 / SAA .25

PHIFER
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403 -1700 USA
Phone: 205.345.2120 • FAX: 205.391.0799
Toll Free USA/Canada: 1.800.221.5497
phifer.com • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.
™ UL, the UL logos and the UL mark are trademarks of UL LLC.
Photo courtesy of Hunter Douglas, South America.
© PHIFER INCORPORATED V20 021420 3035029