



STYLE  
7600 / 7650

7600 - BLACKOUT FABRIC  
7650 - LIGHT-FILTERING FABRIC

---

WEAVING  
EXCELLENCE  
WITH  
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
<b>STYLE 7600 - BLACKOUT</b>							
U90	Bright White	0	46	54	0	0.37	0.26
U97	Coal	0	46	54	0	0.37	0.26



PRODUCT CERTIFIED FOR  
LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



MIF Seal of Approval



STYLE 7600



STYLE 7650

TS = Solar Transmittance  
RS = Solar Reflectance  
AS = Solar Absorptance  
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass  
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally  
Zero-Degree Profile Angle

For additional performance values, test  
references and technical definitions visit us at  
[phifer.com](http://phifer.com).



STYLE  
7600

U90  
Bright White

U99  
Ivory

U91  
Shell

U92  
Khaki

U93  
Dove Grey

U94  
Taupe

U95  
Thunder

U96  
Coffee

U97  
Coal



STYLE  
7650

U90  
Bright White

U99  
Ivory

U91  
Shell

U92  
Khaki

U93  
Dove Grey

U94  
Taupe

U95  
Thunder

U96  
Coffee

U97  
Coal



# STYLE 7600/ 7650 SPECIFICATIONS

With a classic linen pattern face and soft PVC-free backing, Style 7600 combines total light blockage with timeless design. As a light-filtering option, Style 7650 uses the same linen pattern as Style 7600 while allowing filtered natural light to permeate your interior space. These fabrics are suitable for roller shades, Roman shades and panel track systems.

<b>FIRE CLASSIFICATION</b>	California U.S. Title 19 (small scale) BS 5867 Part 2 Type B Performance	NFPA 701 TM#1 (small scale) CAN/ULC-S 109 (large and small scale)
<i>Fire classifications are subject to change. Please go to <a href="http://phifer.com">phifer.com</a> for the most current information.</i>		
<b>BACTERIA AND FUNGAL RESISTANCE</b>	ASTM G21-96	AATCC 174-1998 Part II and III
<b>ENVIRONMENTAL CERTIFICATION</b>	GREENGUARD Certified to these standards for low chemical emissions into indoor air during product usage	GREENGUARD Gold
<b>SAFE USE</b>	RoHS/Directive 2002/95/EC ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101	
<b>WARRANTY</b>	5-year interior	
<b>ACOUSTICAL PERFORMANCE</b>	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a	
<b>UV PROTECTION</b>	Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes	
<b>CLEANING INSTRUCTIONS</b>	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.  <i>Railroading this fabric is not recommended. Colors may vary slightly from swatch samples. All variations are within industry standards.</i>	

STYLE	7600	7650
<b>WIDTHS</b>	118" 300 cm	118" 300 cm
<b>ROLL LENGTH</b>	30 Linear Yards 27.4 Linear Meters	30 Linear Yards 27.4 Linear Meters
<b>COMPOSITION</b>	45% Polyester / 55% Acrylic Foamed Backing	100% Polyester
<b>MESH WEIGHT</b>	11.8 oz/yd <sup>2</sup> 400 g/m <sup>2</sup>	6.2 oz/yd <sup>2</sup> 210 g/m <sup>2</sup>
<b>FABRIC THICKNESS</b>	0.020 in 0.51 mm	0.014 in 0.36 mm
<b>OPENNESS FACTOR</b>	Opaque	Light-filtering
<b>ACOUSTICAL VALUE</b>	NRC .05 / SAA .07	NRC .40 / SAA .44

## PHIFER

INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403-1700 USA  
Phone: 205.345.2120 • FAX: 205.391.0799  
Toll Free USA/Canada: 1.800.221.5497  
[phifer.com](http://phifer.com) • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.  
™ UL, the UL logos and the UL mark are trademarks of UL LLC.  
Photo courtesy of Hunter Douglas, South America.  
© PHIFER INCORPORATED V20 013020 3036596